

# SPMP LED



$\eta_{ef}$  (lm/W)  
95-115

## Bruksområde

- Utenpåliggende armatur for tak/vegg.

## Armatur

- Stål hvitlakkert, RAL 9003.

## Optikk

- Opal eller mikropigmatisk avdekning.

## Bestykning



- LED Osram/Samsung.
- 3000° eller 4000° Kelvin.
- CRI 80 standard (kan leveres med CRI 90).

## Varianter

- Digital dimming (DALI).
- 

Art. nr.	W	Lumen	Kelvin	Ø	X	Y	C	
429215	9	1050	3000	190	120	140	41	Prism.
429222	13	1350	3000	190	120	140	41	Prism.
429224	19	1950	3000	190	120	140	41	Prism.
429216	26	3400	3000	370	200	230	45	Prism.
429221	34	3800	3000	370	200	230	45	Prism.
429228	40	4500	3000	550	400	400	45	Prism.
429213	9	970	3000	190	120	140	41	Opal
429223	13	1350	3000	190	120	140	41	Opal
429225	19	1800	3000	190	120	140	41	Opal
429214	26	2800	3000	370	200	230	45	Opal
429220	34	3550	3000	370	200	230	45	Opal.
429229	40	4100	3000	550	400	400	45	Opal.

Ca. 15% lavere lumen med CRI 90



Armaturen skal aldri tilkobles byggestrøm.  
Armaturen skal primært megges med 250V DC.  
Hvis det benyttes 500V må fasene sammenkobles.